

**pewag**

**STRONG  
IS NOT  
ENOUGH**

[www.pewag.com](http://www.pewag.com)

# pewag levo hook LH

The revolution of load handling

the  
**next**  
generation  
of **hooks**



[levo.pewag.com](http://levo.pewag.com)



**PAVLÍNEK**  
VÁZACÍ PROSTŘEDKY

EMAIL: [OBCHOD@PAVLINEK.CZ](mailto:OBCHOD@PAVLINEK.CZ)  
TEL: +420 595 693 911  
ŠALOUNOVA 746/31, OSTRAVA VÍTKOVICE  
IČ: 25358511 DIČ: CZ25358511



## pewag<sup>red</sup> levo hook LH

### Increased efficiency, combined with outstanding safety and reliability.

Manual process steps such as attaching and releasing hooks require a great deal of time and resources. Automation is a way round it – and that's where pewag comes in.

The pewag levo hook LH is the all-in-one solution for efficient work processes, safe working methods and satisfied employees. The use of our TÜV-certified levo hook reduces the throughput time of a work cycle while increasing the safety for the user and the load at the same time.



#### 100 % safe (ISO 13849)

Accidental opening of the levo hook under load is not possible, secured communication between hook and remote control, Safety factor against break: 4:1



#### Top pewag quality

Patented tool-free locking of the rotation lock, tool-free initial mounting, TÜV-certified, pewag know-how



#### Complete range of services (on-the-job training)

e-learning trainings, pewag expert support during initial operation, repair



#### Cost and time savings thanks to speedy work processes

Up to 8,000 operating cycles without a break, hook opens and closes within 2.5 seconds



### Safety meets performance.

Automated unloading with the pewag levo hook LH eliminates time-intensive manual workflows, which can be performed faster and with optimised use of resources. In addition, the pewag levo hook LH stands for the highest level of health and safety as well as user protection.

The pewag levo hook LH effectively minimises the hazards that users are normally exposed to in a straightforward, safe and automated manner.

#### The pewag levo hook LH

- provides support when working at height or in deep construction pits.
- withstands temperatures that put a strain on the user (-20 °C to +60 °C / -4 °F to +140 °F).
- is a safe partner when it comes to hazards that may be detected too late (e.g. odourless gases in cesspits).
- allows for the targeted use of human resources (crane operator is able to attach and release the load independently).





## pewag levo hook LH

### Safe and automated handling of loads.

The pewag levo hook LH stands for a new generation of lifting devices. Thanks to its powerful features, the process of releasing loads is automated. It is supporting operators in difficult working conditions, for instance when working at height or in hazardous conditions.

In a professional context, operator safety should be the top priority at all times. The pewag levo hook LH makes this a reality: Operated by radio control, the rotatable lifting hook gets perfect grip straightaway and releases the load without manual assistance.


### Basis configuration.



Practicable remote control



Charging station



**pewag levo hook LH 5 tons**

equipped with battery, temperature sensor and data logger, peTAG (for clear product identification) and operating manual

Code	Working load limit [kg]	e [mm]	a [mm]	b1 [mm]	b2 [mm]	d1 [mm]	d2 [mm]	g [mm]	h [mm]	h1 [mm]	w [mm]	Weight [kg/pc.]
LH 5	5,000	460	32	156	220	54	61	29	528	46	142	20.00

Code	Working load limit [lbs]	e [inch]	a [inch]	b1 [inch]	b2 [inch]	d1 [inch]	d2 [inch]	g [inch]	h [inch]	h1 [inch]	w [inch]	Weight [lbs/pc.]
LH 5	11,023	18.11	1.26	6.14	8.66	2.13	2.40	1.14	20.79	1.81	5.59	44.00

### Optional equipment.




**Lighting module**  
fully illuminated working area



**pewag levo manager**  
comprehensive software  
**Weighing module**



**Multiloading Adapter**  
to operate up to 10 charging  
stations in one line



**pewag austria GmbH**

A-8041 Graz, Gaslaternenweg 4, Phone: +43 (0) 50 50 11-0, Fax: +43 (0) 50 50 11-100,  
saleinfo@pewag.com, [www.pewag.com](http://www.pewag.com)

For detailed information:  
[levo@pewag.com](mailto:levo@pewag.com)  
Phone: +43 (0) 664 6200 120

## Standards: pewag levo hook LH

Status: 07.05.2018

**General standards for the hook:**

Mechanical components:

- ISO 9001
- EN 1677
- EN 10204 3.1.B
- Machinery Directive 2006/42/EG

**Electronical components:**

- |                |                     |
|----------------|---------------------|
| • ISO 12100    | EN 61000-4-8        |
| • ISO 13849-1  | EN 61000-6-4        |
| • ISO 13849-2  | EN 61000-6-2        |
| • EN 55011/22  | FCC, 47 CFR Part 15 |
| • EN 61000-4-2 | EN 300220-2         |
| • EN 61000-4-3 | IC RSS-247          |

**Standards for the Charger:**

- IEC 60335
- 55014-1
- 55014-2
- 61000-3-2
- 61000-3-3



**PAVLÍNEK**  
VÁZACÍ PROSTŘEDKY

EMAIL: [OBCHOD@PAVLINEK.CZ](mailto:OBCHOD@PAVLINEK.CZ)  
TEL: +420 595 693 911  
ŠALOUNOVA 746/31, OSTRAVA VÍTKOVICE  
IČ: 25358511 DIČ: CZ25358511

